

420 Tecvin

Rev. 6

Uso recomendado /
Recommended end-use:
CAMISA DE PUNTO
INTERIOR /
KNITTED UNDERWEAR

Composición / Composition:
65% Viscosa FR / Viscose FR
30% M-Aramida / M-Aramide
5% P-Aramida / P-Aramide



420 Tecvin

LIGAMENTO / LIGAMENT	Interlock / Knit	
PESO / WEIGHT (gr/m²)	210 ± 5%	EN 12127
ANCHO / WIDTH (cm)	150 ± 3	
PILLING MARTINDALE (5.000 cycles)	4	EN ISO 12945-2
ENCOGIMIENTO AL LAVADO WASHING SHRINKAGE	5%	EN ISO 6330 / EN ISO 5077
PRETRATAMIENTO / PRE-TREATMENT	Standard requirement	
INFLAMABILIDAD / INFLAMMABILITY	A1-A2	EN ISO 15025 (EN ISO 11612)
CALOR CONVECTIVO / CONVECTIVE HEAT	B1	EN ISO 9151
CALOR RADIANTE / RADIANT HEAT	C1	EN ISO 6942
CALOR POR CONTACTO / CONTACT HEAT	F1	EN ISO 12127-1

420 Tecvin

Rev. 6

Sectores recomendados / Recommended use:



Forestal
Forestry



Cristalera
Glass Foundry



Bomberos
Firemen



Policia
Policemen

Normativas para prenda / Standard for garments:




Instrucciones de lavado EN ISO 6330 (40°C) / Washing instructions EN ISO 6330 (40°C):



*Evitar utilizar suavizantes / Avoid using softeners

Colores disponibles / Available colors:



Crudo
Cream