

625 Orange HV

Rev. 7

Uso recomendado /
Recommended end-use:
POLO HV /
HV POLO SHIRT

Composición / Composition:
40% Acrílica modificada tipo-F / Modified acrylic fibre type-F
40% Poliéster FR / FR Polyester
19% M-Aramida / M-Aramide
1% Antiestático / Antistatic



625 Orange HV

LIGAMENTO / LIGAMENT	Punto liso dos caras / Double face single jersey	
PESO / WEIGHT (gr/m²)	250 ± 5%	EN 12127
ANCHO / WIDTH (cm)	165 ± 5	
ENCOGIMIENTO AL LAVADO / WASHING SHRINKAGE	5%	EN ISO 6330 / EN ISO 5077
PRETRATAMIENTO / PRE-TREATMENT	Standard requirement	
INFLAMABILIDAD / INFLAMMABILITY	A1	EN ISO 15025 (EN ISO 11612)
CALOR CONVECTIVO / CONVECTIVE HEAT	B1	EN ISO 9151
CALOR RADIANTE / RADIANT HEAT	C1	EN ISO 6942
CALOR POR CONTACTO / CONTACT HEAT	F1	EN ISO 12127-1
ANTIESTÁTICO / ANTISTATIC	Pass	EN 1149-3/5
ARCO ELÉCTRICO / ELECTRIC ARC	ATPV: Category I 4kA APC I	ASTM F1959 (NFPA 70 E) EN IEC 61482-1-2
ALTA VISIBILIDAD / HIGH VISIBILITY ¹	Pass ¹	EN ISO 20471 RIS-3279-TOM

¹ También después de 50 lavados según EN ISO 6330 / Also after 50 washing cycles according EN ISO 6330




625 Orange HV

Rev. 7

Sectores recomendados / Recommended use:



Petróleo y gas
Oil & Gas



Electricidad
Electricity



Petroquímicas
Petrochemistry



Ferrocarril
Railway

Normativas para prenda / Standard for garments:



Instrucciones de lavado EN ISO 6330 (40°C) / Washing instructions EN ISO 6330 (40°C):



*Evitar utilizar suavizantes / Avoid using softeners

Colores disponibles / Available colors:



Naranja HV
HV Orange



Rojo HV
HV Red

