

828 Acolchado Xispal RS

Rev. 5

Uso recomendado /
Recommended end-use:
TEJIDOS ACOLCHADOS /
QUILTED FABRIC

Composición / Composition:

42% **Aramida reciclada / Recycled aramid**

29% **Algodón / Cotton**

22,5% **Acrílica modificada tipo-F / Modified acrylic fibre type-F**

6% **Viscosa / Viscose**

0,5% **Antiestático / Antistatic**



| | | |
|---|---------------------------------|---------------------|
| LIGAMENTO / LIGAMENT | IEI Acolchado / Quilted Tafetan | |
| PESO / WEIGHT (gr/m ²) | 250 ± 5% | UNE 40339 |
| ANCHO / WIDTH (cm) | 150 ± 3 | |
| ENCOGIMIENTO AL LAVADO WASHING SHRINKAGE | 5% | UNE-EN ISO 6330 |
| PRETRATAMIENTO / PRE-TREATMENT | Standard requirement | |
| INFLAMABILIDAD INFLAMMABILITY | A1 | EN 15025 (EN 11612) |
| RESISTENCIA AL CALOR (180°C) HEAT RESISTANCE (180°C) | Pass | EN 17493 |
| ANTIESTÁTICO ANTISTATIC | Pass | EN 1149/3/5 |



828 Acolchado Xispal RS


Rev. 5




Sectores recomendados / Recommended use:

FORRO ACOLCHADO / PADDED LINING

Normativas para prenda / Standard for garments:



Instrucciones de lavado EN 6330 (40°C) / Washing instructions EN 6330 (40°C):



*Evitar utilizar suavizantes / Avoid using softeners

Colores disponibles / Available colors:



Negro G328
Black G328