


330 Anti-cut

Rev. 4

Recommended end-use /
Uso recomendado:
CUTTING RISK /
RIESGO AL CORTE

Composition / Composición:
41 % Polyethylene / Polietileno
39% Polyester / Poliéster
20 % Fiberglass / Fibra de vidrio

330 Anti-cut

LIGAMENT LIGAMENTO	Knit / Punto liso	
WEIGHT (oz sq yd) PESO (gr/m ²)	8,70 ± 5% 300 ± 5%	UNE 40339
WIDTH (in) ANCHO (cm)	51 ± 2 130 ± 5	
WASHING SHRINKAGE ENCOGIMIENTO AL LAVADO	5%	UNE-EN ISO 6330
PUNCTURE RESISTANCE RESISTENCIA A LA PERFORACIÓN	Level 3	EN 388
RESISTANCE TO CUTTING BY SHARP OBJECTS TDM (RESISTENCIA AL CORTE POR OBJETOS AFILADOS)	Level E	EN 388
TEAR RESISTANCE RESISTENCIA AL RASGADO	Level 4	EN 388
ABRASION RESISTANCE RESISTENCIA A LA ABRASIÓN	Level 1	EN 388
GLOBAL AND SPECIFIC MIGRATION IN FOOD MIGRACIÓN GLOBAL Y ESPECÍFICA EN ALIMENTOS	Pass	EN 1186 

330 Anti-cut

Rev. 4

Recommended use / Sectores recomendados:



Glass Foundry
Cristalera



Food industry
Alimentos

Standard for garments / Normativas para prenda:



Washing instructions EN 6330 (86°F) / Instrucciones de lavado EN 6330 (30°C):



*Avoid using softeners / Evitar utilizar suavizantes

Available colors / Colores disponibles:



White
Blanco



Negro
Black