

Arc Flash Solutions

Soluciones frente al Arco Eléctrico

Rev.10

ASTM F1959 / NFPA 70E

| | |
|--------------|-------------------------------------|
| Category I | ATPV 4 < 8 (cal/cm ²) |
| Category II | ATPV 8 < 25 (cal/cm ²) |
| Category III | ATPV 25 < 40 (cal/cm ²) |
| Category IV | ATPV ≥ 40 (cal/cm ²) |

Single Fabric

| | |
|---------------------|-------------|
| 816 Xispal RS | Category I |
| 822 RI Xispal | Category II |
| 825 Xispal RS | Category II |
| 825 RI CL Xispal RS | Category II |
| 826 Xispal RS | Category II |
| 830 Xispal RS | Category II |
| 834 Xispal RS | Category II |
| 838 Xispal RS | Category II |
| 843 Xispal RS | Category II |
| 844 Denim Xispal RS | Category II |
| Cardigan Xispal RS | Category II |
| 918 Valen-t | Category II |
| 919 Valen-t | Category II |
| 936 Valen-t | Category II |
| 937 Valen-t | Category II |
| 945 Valen-t | Category II |

EN 61482-1-1

| Single Fabric | ATPV (cal/cm ²) | ELIM (cal/cm ²) |
|------------------|--------------------------------|--------------------------------|
| 816 Xispal RS | 6,4 | 4,8 |
| 822 RI Xispal RS | 6,7 | 4,5 |
| 825 Xispal RS | 9,60 | 8,60 |
| 830 Xispal RS | 12,00 | 10,00 |
| 834 Xispal RS | 14,00 | 10,00 |
| 838 Xispal RS | 19,00 | 16,00 |
| 919 Valen-t | 11,00 | 9,90 |
| 936 Valen-t | 9,5 | 8,10 |
| 945 Valen-t | 18,00 | 13,00 |

EN 61482-1-2

APC 1 - 4kA

427 Tecvin
816 Xispal RS
817 RI Waterproof Xispal RS
822 RI Xispal RS
825 Xispal RS
826 Xispal RS
830 Xispal RS
834 Xispal RS
838 Xispal RS
843 Xispal RS
Cardigan Xispal RS
919 Valen-t
936 Valen-t
937 Valen-t

(s) Scouting

APC 2 - 7kA

825 Xispal RS + 816 Xispal RS
830 Xispal RS + 816 Xispal RS
838 Xispal RS + 822 Xispal RS
945 Valen-t



MADE IN MEXICO