

**356**

Rev. 3

Uso recomendado /  
Recommended end-use:  
FUNDAS Y RECUBRIMIENTOS /  
COVERS

Composición / Composition :  
**75 % P-Aramida / P-Aramide**  
**25 % Siloxane metalizado / Metalized Siloxane**

LIGAMENTO / LIGAMENT	Sarga / Twill	
PESO / WEIGHT (gr/m <sup>2</sup> )	550 ± 5%	UNE 40339
ANCHO / WIDTH (cm)	130 ± 3	
PILLING MARTINDALE (5.000 cycles)	5	EN 12945-2
RESISTENCIA A LA TRACCIÓN (N U x T) TENSILE STRENGTH (N W x F)	3400 ± 5% 3300 ± 5%	UNE-EN ISO 13934-1
ENCOGIMIENTO AL LAVADO WASHING SHRINKAGE	3%	UNE-EN ISO 15797
INFLAMABILIDAD / INFLAMMABILITY	A1-A2	EN 15025

356

Rev. 3

Sectores recomendados / Recommended use:

AUTOMOCIÓN

Normativas para prenda / Standard for garments:



Instrucciones de lavado EN 15797 (75°C) / Washing instructions EN 15797 (75°C):



Colores disponibles / Available colors:



Silver