

828 Acolchado Xispal RS

Rev. 4

Uso recomendado /
Recommended end-use:
TEJIDOS ACOLCHADOS /
QUILTED FABRIC

Composición / Composition:
42% **Aramida reciclada / Recycled aramid**
29% **Algodón / Cotton**
22,5% **Acrílica modificada tipo-F / Modified acrylic fibre type-F**
6% **Viscosa / Viscose**
0,5% **Antiestático / Antistatic**



828 Acolchado Xispal RS

LIGAMENTO / LIGAMENT	IEI Acolchado / Quilted Tafetan	
PESO / WEIGHT (gr/m²)	250 ± 5%	UNE 40339
ANCHO / WIDTH (cm)	150 ± 3	
ENCOGIMIENTO AL LAVADO WASHING SHRINKAGE	5%	UNE-EN ISO 6330
PRETRATAMIENTO / PRE-TREATMENT	Standard requirement	
INFLAMABILIDAD INFLAMMABILITY	A1	EN 15025 (EN 11612)
RESISTENCIA AL CALOR (180°C) HEAT RESISTANCE (180°C)	Pass	EN 17493
ANTIESTÁTICO ANTISTATIC	Pass	EN 1149-3-5



828 Acolchado Xispal RS

Rev. 4


Sectores recomendados / Recommended use:

FORRO ACOLCHADO / PADDED LINING

Normativas para prenda / Standard for garments:



Instrucciones de lavado EN 6330 (40°C) / Washing instructions EN 6330 (40°C):



*Evitar utilizar suavizantes / Avoid using softeners

Colores disponibles / Available colors:



Negro G328
Black G328