

Arc Flash Solutions

Soluciones frente al Arco Eléctrico

Rev. 7

ASTM F1959 / NFPA 70E

Category I	$4 \geq \text{ATPV (cal/cm}^2) < 8$
Category II	$8 \geq \text{ATPV (cal/cm}^2) < 25$
Category III	$25 \geq \text{ATPV (cal/cm}^2) < 40$
Category IV	$\text{ATPV (cal/cm}^2) \geq 40$

Single Fabric	Multilayer Fabric
816 Xispal RS Category I	925 Valen-t + 816 Xispal RS Category III
822 RI Xispal Category II	925 Valen-t + 825 Xispal RS Category III
825 Xispal RS Category II	925 Valen-t + 828 Acolchado Xispal RS (s) Category IV
825 RI CL Xispal RS Category II	925 Valen-t + 919 Valen-t (s) Category III
826RI Xispal RS Category II	925 Valen-t + 925 Valen-t (s) Category III
830 Xispal RS Category II	
834 Xispal RS Category II	
838 Xispal RS Category II	
843 Xispal RS Category II	
Cardigan Xispal RS Category II	
918 Valen-t Category II	
919 Valen-t Category II	
925 Valen-t Category II	
936 Valen-t Category II	
937 Valen-t Category II	
945 Valen-t Category II	

EN 61482-1-1

Single Fabric	ATPV (cal/cm ²)	ELIM (cal/cm ²)
816 Xispal RS	6,40	4,80
822 RI Xispal RS	6,70	4,50
825 Xispal RS	9,60	8,60
830 Xispal RS	12,00	9,00
919 Valen-t	11,00	9,90
936 Valen-t	9,5	8,10

EN 61482-1-2

APC 1 - 4kA

816 Xispal RS
822 RI Xispal RS
825 Xispal RS
830 Xispal RS
834 Xispal RS
838 Xispal RS
843 Xispal RS
919 Valen-t
925 Valen-t
936 Valen-t
937 Valen-t

APC 2 - 7kA

825 Xispal RS + 816 Xispal RS
825 Xispal RS + 817RI Xispal RS
830 Xispal RS + 816 Xispal RS
925 Valen-t + 919 Valen-t
945 Valen-t

(s) Scouting



MADE IN MEXICO