

	
BLUE 70	GREEN 40
	
BLACK G328	RED 30
	
BLUE 60	ORANGE 20
	
GREY 82	ORANGE HV
	
GREY 80	RAW N422
	
GREY 113	YELLOW 10
	
BROWN N420	YELLOW HV
	
BLUE 50	



FIBER	M-Aramida / M-Aramide			P-Aramida / P-Aramide
TÍTULO / YARN COUNT (Nm) (TEX)	2/85Nm 24	3/40Nm 75	3/70Nm 42,5	3/50 Nm 60
Valor (Coef. de variación) Value (Variation coefficient)				
RESISTENCIA DE ROTURA BREAKING STRENGTH (gr)	750 (10.82 %)	2150 (5.9 %)	1500 (7.5%)	8100 (5%)
ALARGAMIENTO ELONGATION (%)	18 (5 %)	20 (5 %)	18 (5%)	18 (5%)
TORSIONES T/M (V/m)	910 (5 %)	580 (5 %)	625 (5%)	625 (5%)
RKM (cN/Tex)	31	28	35	125
SOLIDEZ A LOS LAVADOS (60°C) COLOUR FASTNESS TO WASHES (60°C)	4/5	4/5	4/5	-
SOLIDEZ AL FROTE (Húmedo y Seco) COLOUR FASTNESS TO RUBBING (Dry and Wet)	4	4	4	-
SOLIDEZ A LA LUZ ARTIFICIAL COLOUR FASTNESS TO ARTIFICIAL LIGHT	2/3	2/3	2/3	-
TAMAÑO DE AGUJA RECOMENDADO NEEDLE SIZE RECOMMENDED (Nm)	70 - 90	110 - 130	90 - 110	110 - 130
APLICACIÓN APPLICATION	Embroidery	Industrial textiles, automotive, home interior	Apparel, automotive	Fire fighters, Ballistic protection, Cut protection gloves, Filtration.
TINTURA DYE	Posibilidad de tintura de colores especiales. Dyeble possibility of special colours.			-

Made by Jone! S.L



Este hilado es clasificado como hilo ignífugo por la naturaleza de su composición. /
This thread is classified by flame retardant property for its natural fibres.

lenard
Technical Fabrics

HILOS DE COSER ESPECIALES /
SPECIAL SEWING THREADS

Hilos IGNÍFUGOS
FR Threads

EASY WORKS

Composición/composition:
100% Aramida / Aramide