

460 Tecvin

Rev. 1

Uso recomendado /
Recommended end-use:
COMPLEMENTO DE
CONFECCIÓN: PUÑOS,
CUELLOS / MANUFACTURED
COMPLEMENT: CUFFS, NECKS

Composición / Composition:
93% M-Aramida / M-Aramide
5% P-Aramida / P-Aramide
2% Antiestático / Antistatic



460 Tecvin

LIGAMENTO / LIGAMENT	Canalé / Rib Knit	
PESO / WEIGHT (gr/m ²)	600 ± 5%	EN 12127
ANCHO / WIDTH (cm)	68 ± 3 Tubular	
PILLING MARTINDALE (5.000 cycles)	4	EN ISO 12945-2
ENCOGIMIENTO AL LAVADO WASHING SHRINKAGE	5%	EN ISO 6330 / EN ISO 5077
PRETRATAMIENTO / PRE-TREATMENT	Standard	
INFLAMABILIDAD / INFLAMMABILITY	A1 - A2	EN ISO 15025 (EN ISO 11612)
CALOR CONVECTIVO / CONVECTIVE	B2	EN ISO 9151
CALOR RADIANTE / RADIANT	C2	EN ISO 6942
CALOR POR CONTACTO / CONTACT HEAT	F2	EN ISO 12127-1
ANTIESTÁTICO / ANTISTATIC	Pass	EN 1149-3/5
FORESTAL / FOREST MEN	Pass	EN ISO 15384

460 Tecvin

Rev. 1

Sectores recomendados / Recommended use:

COMPLEMENTO DE CONFECCIÓN// MANUFACTURED COMPLEMENT



Policia
Policemen




Forestal
Forestmen

Normativas para prenda / Standard for garments:



Instrucciones de lavado EN ISO 6330 (60°C) / Washing instructions EN ISO 6330 (60°C) :



*Evitar utilizar suavizantes / Avoid using softeners

Colores disponibles / Available colors:



Marino DOPED DYED
Navy Blue DOPED DYED

Otros colores consultar al Departamento Comercial.
Other colours ask to Sales Department.